

2.4mm Plug to 2.4mm Plug, KF141HP Microwave Cable, 915mm

141HPX-24M24M-915**FEATURES**

- Suitable up to 40GHz
- Excellent Return Loss & Insertion Loss
- Ultra Low Loss, Phase Stable & Amplitude Stable
- 100% VNA Tested; supplied with serialised performance plots
- Heavy Duty Sleeving for Reliability and Robustness

**MATERIAL SPECIFICATION**

Cable Series	GTx KF141HP, Microwave Coaxial Cable
Connector 1	2.4mm Straight Plug, Stainless Steel
Connector 2	2.4mm Straight Plug, Stainless Steel
Length	915mm (Tip to Tip)
Cable Overall Diameter	3.60mm
Armour	None

ELECTRICAL SPECIFICATION

Impedance	50 Ohms
Max. Frequency	40 GHz
VSWR	1.30 @40 GHz
Insertion Loss	3.45dB @40 GHz
Velocity of Propagation	74%
Voltage Withstanding	500V RMS Maximum
Shielding Effectiveness	> 90dB

MECHANICAL & ENVIRONMENTAL SPECIFICATION

Bending Radius (static)	18mm
Bending Radius (flexing)	36mm
Cable Weight	33 gms/m
RoHS Compliant	Yes
Temperature Range	-55 to +165 degrees C