

2.92mm Plug to 2.92mm Plug, KF141UF Microwave Cable, 915mm

141UFX-29M29M-915

FEATURES

- Suitable up to 40GHz
- Excellent Return Loss & Insertion Loss
- Ultra Low Loss, Phase Stable & Amplitude Stable
- 100% VNA Tested; supplied with serialised performance plots
- Heavy Duty Sleeving for Reliability and Robustness



MATERIAL SPECIFICATION

Cable Series	GTx KF141UF, Microwave Coaxial Cable
Connector 1	2.92mm Straight Plug, Stainless Steel
Connector 2	2.92mm Straight Plug, Stainless Steel
Length	915mm (Tip to Tip)
Cable Overall Diameter	3.6mm
Armour	None

ELECTRICAL SPECIFICATION

Impedance	50 Ohms
Max. Frequency	40 GHz
VSWR	1.30 @40 GHz
Insertion Loss	4.32dB @40 GHz
Velocity of Propagation	76%
Voltage Withstanding	450V RMS Maximum
Shielding Effectiveness	> 90dB

MECHANICAL & ENVIRONMENTAL SPECIFICATION

Bending Radius (static)	14mm
Bending Radius (flexing)	36mm
Cable Weight	30 gms/m
RoHS Compliant	Yes
Temperature Range	-55 to +85 degrees C