

2.9mm Plug to 2.9mm Plug, KF157UHP Microwave Cable, 915mm

157UHPX-29M29M-915

FEATURES

- Suitable up to 40GHz
- Excellent Return Loss & Insertion Loss
- Ultra Low Loss, Phase Stable & Amplitude Stable
- 100% VNA Tested; supplied with serialised performance plots
- Heavy Duty Sleaving for Reliability and Robustness



MATERIAL SPECIFICATION

Cable Series	GTx KF157UHP, Microwave Coaxial Cable
Connector 1	2.9mm Straight Plug, Stainless Steel
Connector 2	2.9mm Straight Plug, Stainless Steel
Length	915mm (Tip to Tip)
Cable Overall Diameter	3.9mm
Armour	None

ELECTRICAL SPECIFICATION

Impedance	50 Ohms
Max. Frequency	40 GHz
VSWR	1.35 @40 GHz
Insertion Loss	2.73dB @40 GHz
Velocity of Propagation	83%
Voltage Withstanding	800V RMS Maximum
Shielding Effectiveness	> 90dB

MECHANICAL & ENVIRONMENTAL SPECIFICATION

Bending Radius (static)	20mm
Bending Radius (flexing)	39mm
Cable Weight	41 gms/m
RoHS Compliant	Yes
Temperature Range	-55 to +165 degrees C